Turbulence and CFD models: Theory and applications

Roadmap to Lecture 5

- 1. Governing equations of fluid dynamics
- 2. RANS equations Reynolds averaging
- 3. The Boussinesq hypothesis
- 4. The gradient diffusion hypothesis
- 5. Sample turbulence models

Roadmap to Lecture 5

1. Governing equations of fluid dynamics

- 2. RANS equations Reynolds averaging
- 3. The Boussinesq hypothesis
- 4. The gradient diffusion hypothesis
- 5. Sample turbulence models

"That we have written an equation does not remove from the flow of fluids its charm or mystery or its surprise."

Richard Feynman

Governing equations of fluid dynamics

$$\begin{aligned} \frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \mathbf{u}) &= 0 \\ \frac{\partial (\rho \mathbf{u})}{\partial t} + \nabla \cdot (\rho \mathbf{u} \mathbf{u}) &= -\nabla p + \nabla \cdot \tau + \mathbf{S}_{\mathbf{u}} \longleftarrow \mathbf{S}_{\mathbf{u}} & \mathbf{S}_{\mathbf{u}} & \mathbf{s}_{\mathbf{u}} \\ \frac{\partial (\rho e_t)}{\partial t} + \nabla \cdot (\rho e_t \mathbf{u}) &= -\nabla \cdot q - \nabla \cdot (p \mathbf{u}) + \tau \mathbf{v} \nabla \mathbf{u} + \mathbf{S}_{e_t} \\ + \end{aligned}$$

Additional equations to close the system

Relationships between two or more thermodynamics variables (p, ρ, T, e_t) Additionally, relationships to relate the transport properties (μ, k)

• In the absent of models (turbulence, multiphase, mass transfer, combustion, particles interaction, chemical reactions, acoustics, and so on), this set of equations will resolve all scales in space and time.

Governing equations of fluid dynamics

• I like to write the governing equations in matrix-vector form.

$$\frac{\partial \mathbf{q}}{\partial t} + \frac{\partial \mathbf{e}_i}{\partial x} + \frac{\partial \mathbf{f}_i}{\partial y} + \frac{\partial \mathbf{g}_i}{\partial z} = \frac{\partial \mathbf{e}_v}{\partial x} + \frac{\partial \mathbf{f}_v}{\partial y} + \frac{\partial \mathbf{g}_v}{\partial z}$$

• Where **q** is the vector of the conserved flow variables,

$$\mathbf{q} = \begin{bmatrix} \rho \\ \rho u \\ \rho v \\ \rho v \\ \rho w \\ \rho e_t \end{bmatrix} \longleftarrow \mathbf{ME}$$

Governing equations of fluid dynamics

• I like to write the governing equations in matrix-vector form.

$$\frac{\partial \mathbf{q}}{\partial t} + \frac{\partial \mathbf{e}_i}{\partial x} + \frac{\partial \mathbf{f}_i}{\partial y} + \frac{\partial \mathbf{g}_i}{\partial z} = \frac{\partial \mathbf{e}_v}{\partial x} + \frac{\partial \mathbf{f}_v}{\partial y} + \frac{\partial \mathbf{g}_v}{\partial z}$$

The vectors e_i, f_i, and g_i contain the inviscid fluxes (or convective fluxes) in the x, y, and z directions,

$$\mathbf{e}_{i} = \begin{bmatrix} \rho u \\ \rho u^{2} + p \\ \rho uv \\ \rho uw \\ (\rho e_{t} + p) u \end{bmatrix}, \quad \mathbf{f}_{i} = \begin{bmatrix} \rho v \\ \rho vu \\ \rho vu \\ \rho v^{2} + p \\ \rho vw \\ (\rho e_{t} + p) v \end{bmatrix}, \quad \mathbf{g}_{i} = \begin{bmatrix} \rho w \\ \rho wu \\ \rho wu \\ \rho wv \\ \rho w^{2} + p \\ (\rho e_{t} + p) w \end{bmatrix} \leftarrow \mathbf{EE}$$

Governing equations of fluid dynamics

• I like to write the governing equations in matrix-vector form.

$$\frac{\partial \mathbf{q}}{\partial t} + \frac{\partial \mathbf{e}_i}{\partial x} + \frac{\partial \mathbf{f}_i}{\partial y} + \frac{\partial \mathbf{g}_i}{\partial z} = \frac{\partial \mathbf{e}_v}{\partial x} + \frac{\partial \mathbf{f}_v}{\partial y} + \frac{\partial \mathbf{g}_v}{\partial z}$$

The vectors e_v, f_v, and g_v contain the viscous fluxes (or diffusive fluxes) in the x, y, and z directions,



Governing equations of fluid dynamics

The heat fluxes q in the vectors e_v, f_v, and g_v can be computed using Fourier's law of heat conduction as follows,

$$q_x = -k \ \frac{\partial T}{\partial x}, \qquad q_y = -k \ \frac{\partial T}{\partial y}, \qquad q_z = -k \ \frac{\partial T}{\partial z}$$
 Where *k* is the thermal conductivity

• If we assume that the fluid behaves as a Newtonian fluid (a fluid where the shear stresses are proportional to the velocity gradients $\tau \propto \mu \nabla \mathbf{u}$), the viscous stresses can be computed as follows,

$$\tau_{xx} = \lambda \left(\nabla \cdot \mathbf{u} \right) + 2\mu \frac{\partial u}{\partial x} = \frac{2}{3}\mu \left(2\frac{\partial u}{\partial x} - \frac{\partial v}{\partial y} - \frac{\partial w}{\partial z} \right) \qquad \tau_{xy} = \tau_{yx} = \mu \left(\frac{\partial v}{\partial x} + \frac{\partial u}{\partial y} \right) \tau_{yy} = \lambda \left(\nabla \cdot \mathbf{u} \right) + 2\mu \frac{\partial v}{\partial y} = \frac{2}{3}\mu \left(2\frac{\partial v}{\partial y} - \frac{\partial u}{\partial x} - \frac{\partial w}{\partial z} \right) \qquad \tau_{xz} = \tau_{zx} = \mu \left(\frac{\partial w}{\partial x} + \frac{\partial u}{\partial z} \right) \tau_{zz} = \lambda \left(\nabla \cdot \mathbf{u} \right) + 2\mu \frac{\partial w}{\partial z} = \frac{2}{3}\mu \left(2\frac{\partial w}{\partial z} - \frac{\partial u}{\partial x} - \frac{\partial v}{\partial y} \right) \qquad \tau_{yz} = \tau_{zy} = \mu \left(\frac{\partial w}{\partial y} + \frac{\partial v}{\partial z} \right)$$

Governing equations of fluid dynamics

- In virtually all practical aerodynamic problems, the working fluid can be assumed to be Newtonian.
- In the normal viscous stresses $\tau_{xx}, \tau_{yy}, \tau_{zz}$, the variable λ is known as the second viscosity coefficient (or bulk viscosity).
- If we use Stokes hypothesis, the second viscosity coefficient can be approximated as follows,

$$\lambda = -\frac{2}{3}\mu$$

- Except for extremely high temperature or pressure, there is so far no experimental evidence that Stokes hypothesis does not hold.
- For gases and incompressible flows, Stokes hypothesis is a good approximation.

Governing equations of fluid dynamics

 By using Stokes hypothesis and assuming a Newtonian flow, the viscous stresses can be expressed as follows,

$$\tau_{xx} = \frac{2}{3}\mu \left(2\frac{\partial u}{\partial x} - \frac{\partial v}{\partial y} - \frac{\partial w}{\partial z} \right), \qquad \tau_{xy} = \tau_{yx} = \mu \left(\frac{\partial v}{\partial x} + \frac{\partial u}{\partial y} \right)$$
$$\tau_{yy} = \frac{2}{3}\mu \left(2\frac{\partial v}{\partial y} - \frac{\partial u}{\partial x} - \frac{\partial w}{\partial z} \right), \qquad \tau_{xz} = \tau_{zx} = \mu \left(\frac{\partial w}{\partial x} + \frac{\partial u}{\partial z} \right)$$
$$\tau_{zz} = \frac{2}{3}\mu \left(2\frac{\partial w}{\partial z} - \frac{\partial u}{\partial x} - \frac{\partial v}{\partial y} \right), \qquad \tau_{yz} = \tau_{zy} = \mu \left(\frac{\partial w}{\partial y} + \frac{\partial v}{\partial z} \right)$$

- In our discussion, it is also necessary to relate the transported fluid properties (μ, k) to the thermodynamic variables (temperature and pressure).
 - We will discuss this later.

Governing equations of fluid dynamics

• If you examine closely the equations we have seen so far, you will notice that we have five equations and seven variables.

$$\begin{aligned} \frac{\partial \rho}{\partial t} + \nabla \cdot (\rho \mathbf{u}) &= 0 \\ \frac{\partial (\rho \mathbf{u})}{\partial t} + \nabla \cdot (\rho \mathbf{u} \mathbf{u}) &= -\nabla p + \nabla \cdot \tau + \mathbf{S}_{\mathbf{u}} \longleftarrow \mathbf{S}_{\mathbf{u}} & \downarrow \\ \frac{\partial (\rho e_t)}{\partial t} + \nabla \cdot (\rho e_t \mathbf{u}) &= -\nabla \cdot q - \nabla \cdot (p \mathbf{u}) + \tau : \nabla \mathbf{u} + \mathbf{S}_{e_t} \end{aligned}$$

• To close the system, we need to find two more equations by determining the relationship that exist between the thermodynamics variables (p, ρ, T, e_t) .

Governing equations of fluid dynamics

- Choosing the internal energy e_i and the density ρ as the two independent thermodynamic variables, we can find equations of state of the form,

$$p = p(e_i, \rho)$$
 $T = T(e_i, \rho)$

• Assuming that the working fluid is a gas that behaves as a perfect gas and is also a calorically perfect gas, the following relations for pressure *p* and temperature *T* can be used,

$$p = (\gamma - 1) \rho e_i, \qquad T = \frac{p}{\rho R_g} = \frac{(\gamma - 1) e_i}{R_g}$$

- Now our system of equations is closed.
- That is, seven equations and seven variables.

Governing equations of fluid dynamics

• To derive the thermodynamics relations for pressure *p* and temperature *T*, the following equations where used,

$$p = \rho R_g T$$
Equation of state
$$e_i = c_v T, \qquad h = c_p T, \qquad \gamma = \frac{c_p}{c_v}, \qquad c_v = \frac{R_g}{\gamma - 1}, \qquad c_p = \frac{\gamma R_g}{\gamma - 1}$$
Internal energy
Enthalpy
Ratio of specific heat at constant volume
$$e_t = e_i + \frac{1}{2} \left(u^2 + v^2 + w^2 \right)$$

Total energy

Governing equations of fluid dynamics

- In our discussion, it is also necessary to relate the transported fluid properties (μ, k) to the thermodynamic variables.
- The molecular viscosity (or laminar viscosity) can be computed using Sutherland's formula with two coefficients (one of the many models available),

$$\mu = \frac{C_1 T^{\frac{3}{2}}}{(T+C_2)}$$

• The thermal conductivity *k* can be computed as follows,

$$k=rac{c_p\mu}{Pr}$$
 ---- Molecular Prandtl number of the working fluid

Governing equations of fluid dynamics

- If you are working with high-speed compressible flows, it is useful to introduce the Mach number.
- The Mach number is a non-dimensional parameter that measures the speed of the gas motion in relation to the speed of sound a,

$$a = \left[\left(\frac{\partial p}{\partial \rho} \right)_S \right]^{\frac{1}{2}} = \sqrt{\gamma \frac{p}{\rho}} = \sqrt{\gamma R_g T}$$

• Then, the Mach number M can be computed as follows,

$$M_{\infty} = \frac{U_{\infty}}{a} = \frac{U_{\infty}}{\sqrt{\gamma(p/\rho)}} = \frac{U_{\infty}}{\sqrt{\gamma R_g T}}$$

Governing equations of fluid dynamics

• And never forget the definition of the Reynolds number,



- Where *U* is a characteristic velocity, *e.g.*, free-stream velocity.
- And *L* is representative length scale, *e.g.*, length, height, diameter, etc.
- It is well known that the Reynolds number characterizes if the flow is laminar or turbulent.

Governing equations of fluid dynamics

• In the previous set of equations, we introduced two non-dimensional numbers, namely, the Mach number (M) and the Reynolds number (Re).

$$M_{\infty} = \frac{U_{\infty}}{a} = \frac{U_{\infty}}{\sqrt{\gamma(p/\rho)}} = \frac{U_{\infty}}{\sqrt{\gamma R_g T}} \qquad \qquad Re_L = \frac{\rho UL}{\mu} = \frac{UL}{\nu}$$

- In many situations, when simulating or experimenting with scaled models we want to maintain the dynamic similarity between the Mach number and the Reynolds number.
- To do so, we need to adjust the physical properties of the fluid (the fluid density or the fluid viscosity) or the reference pressure in order to maintain dynamic similarity.
- Doing so when conducting CFD simulations is relatively easy.
- However, in physical experiments, this not so easy because it requires specialized pressurized winds tunnels that can maintain the temperature at a constant level, or test facilities that can use different working fluids, e.g., nitrogen, R-134a, and so on.
- In Appendix 1, we go thru some of the algebra used to maintain dynamic similarity when working with the Mach number and the Reynolds number with scaled models.

Governing equations of fluid dynamics

- The previous equations, together with appropriate equations of state, thermodynamics closure models, boundary conditions, and initial conditions, govern the unsteady three-dimensional motion of a viscous Newtonian compressible fluid.
- These equations solve all the scales in space and time.
 - Therefore, we need to use very fine meshes and very small time-steps.
- Notice that besides the thermodynamics models (or constitutive equations) and a few assumptions (Newtonian fluid and Stokes hypothesis), we did not use any other model.
- Our goal now is to add turbulence models to these equations in order to avoid solving all scales.
- This will allow us use coarse meshes and larger time-steps.
 - Therefore, we will be able to get economical solutions.
 - With good accuracy (if good standard practices are followed).
- Before deriving the RANS/URANS equations, let us introduce a few simplifications to this beautiful set of equations.

Simplifications of the governing equations of fluid dynamics

- In many applications the fluid density can be assumed to be constant.
- If the flow is also isothermal, the viscosity is also constant.
- This is true not only for liquids, but also for gases if the Mach number is below 0.3.
- Such flows are known as incompressible flows.
- If the fluid is also Newtonian, the governing equations written in compact (vector notation) conservation differential form and in primitive variable formulation (u, v, w, p) reduce to the following set of equations,

$$\nabla \cdot (\mathbf{u}) = 0$$
$$\frac{\partial \mathbf{u}}{\partial t} + \nabla \cdot (\mathbf{u}\mathbf{u}) = \frac{-\nabla p}{\rho} + \nu \nabla^2 \mathbf{u}$$

Simplifications of the governing equations of fluid dynamics

 In expanded three-dimensional Cartesian coordinates, the simplified governing equations can be written as follows,

$$\frac{\partial u}{\partial x} + \frac{\partial v}{\partial y} + \frac{\partial w}{\partial z} = 0$$

$$\frac{\partial u}{\partial t} + \frac{\partial uu}{\partial x} + \frac{\partial uv}{\partial y} + \frac{\partial uw}{\partial z} = -\frac{1}{\rho}\frac{\partial p}{\partial x} + \nu \left(\frac{\partial^2 u}{\partial x^2} + \frac{\partial^2 u}{\partial y^2} + \frac{\partial^2 u}{\partial z^2}\right)$$

$$\frac{\partial v}{\partial t} + \frac{\partial uv}{\partial x} + \frac{\partial vv}{\partial y} + \frac{\partial vw}{\partial z} = -\frac{1}{\rho}\frac{\partial p}{\partial y} + \nu \left(\frac{\partial^2 v}{\partial x^2} + \frac{\partial^2 v}{\partial y^2} + \frac{\partial^2 v}{\partial z^2}\right)$$

$$\frac{\partial w}{\partial t} + \frac{\partial uw}{\partial x} + \frac{\partial vw}{\partial y} + \frac{\partial ww}{\partial z} = -\frac{1}{\rho}\frac{\partial p}{\partial z} + \nu \left(\frac{\partial^2 w}{\partial x^2} + \frac{\partial^2 w}{\partial y^2} + \frac{\partial^2 w}{\partial z^2}\right)$$

- It is worth noting that the simplifications added do not make the equations easier to solve.
- The mathematical complexity is the same.
- We just eliminated a few variables, so from the computational point of few, it means less storage.
- Also, the convergence rate is not necessarily faster.

Simplifications of the governing equations of fluid dynamics

• We can write the simplified governing equations in matrix-vector form as follows,

$$\frac{\partial \mathbf{q}}{\partial t} + \frac{\partial \mathbf{e}_i}{\partial x} + \frac{\partial \mathbf{f}_i}{\partial y} + \frac{\partial \mathbf{g}_i}{\partial z} = \frac{\partial \mathbf{e}_v}{\partial x} + \frac{\partial \mathbf{f}_v}{\partial y} + \frac{\partial \mathbf{g}_v}{\partial z}$$

$$\mathbf{q} = \begin{bmatrix} 0\\ u\\ v\\ w \end{bmatrix} \qquad \mathbf{e}_{i} = \begin{bmatrix} u\\ u^{2}+p\\ uv\\ uw \end{bmatrix}, \qquad \mathbf{f}_{i} = \begin{bmatrix} v\\ vu\\ v^{2}+p\\ vw \end{bmatrix}, \qquad \mathbf{g}_{i} = \begin{bmatrix} w\\ wu\\ wv\\ w^{2}+p \end{bmatrix}$$

$$\mathbf{e}_{\boldsymbol{v}} = \begin{bmatrix} 0\\ \tau_{xx}\\ \tau_{xy}\\ \tau_{xz} \end{bmatrix}, \qquad \mathbf{f}_{\boldsymbol{v}} = \begin{bmatrix} 0\\ \tau_{yx}\\ \tau_{yy}\\ \tau_{yz} \end{bmatrix}, \qquad \mathbf{g}_{\boldsymbol{v}} = \begin{bmatrix} 0\\ \tau_{zx}\\ \tau_{zy}\\ \tau_{zz} \end{bmatrix}$$

Simplifications of the governing equations of fluid dynamics

• Recall that the viscous stress tensor $\, au\,$ can be written as follows,

$$oldsymbol{ au} = egin{bmatrix} au_{xx} & au_{xy} & au_{xz} \ au_{yx} & au_{yy} & au_{yz} \ au_{zx} & au_{zy} & au_{zz} \end{bmatrix}$$

 By using Stokes hypothesis and assuming a Newtonian flow, the viscous stresses can be expressed as follows,

$$\tau_{xx} = 2\mu \frac{\partial u}{\partial x} \qquad \tau_{xy} = \tau_{yx} = \mu \left(\frac{\partial v}{\partial x} + \frac{\partial u}{\partial y} \right)$$

$$\tau_{yy} = 2\mu \frac{\partial v}{\partial y} \qquad \tau_{xz} = \tau_{zx} = \mu \left(\frac{\partial w}{\partial x} + \frac{\partial u}{\partial z} \right)$$

$$\tau_{zz} = 2\mu \frac{\partial w}{\partial z} \qquad \tau_{yz} = \tau_{zy} = \mu \left(\frac{\partial w}{\partial y} + \frac{\partial v}{\partial z} \right)$$

Simplifications of the governing equations of fluid dynamics

• The viscous stress tensor can be written in compact vector form as follows,

$$\tau = 2\mu \mathbf{S}$$

Where S represents the strain-rate tensor and is given by the following relationship,

$$\mathbf{S} = rac{1}{2} \left[
abla \mathbf{u} +
abla \mathbf{u}^{\mathrm{T}}
ight]$$

 Additionally, the gradient tensor can be decomposed in symmetric (strain-rate tensor) and skew parts (spin tensor) as follows,

$$\nabla \mathbf{u} = [\mathbf{S} + \Omega]$$

• Where Ω represents the spin tensor (vorticity), and is given by,

$$\Omega = \frac{1}{2} \left[\nabla \mathbf{u} - \nabla \mathbf{u}^{\mathrm{T}} \right]$$

Simplifications of the governing equations of fluid dynamics

- In the previous definitions, **S** represent the symmetric part of the gradient tensor and Ω represents the anti-symmetric (or skew) part of the gradient tensor.
- This decomposition is based on the fact that every second rank tensor **A** (*e.g.*, the gradient of a vector), can be decomposed into symmetric and skew parts, as follows,

$$\mathbf{A} = \frac{1}{2} \begin{bmatrix} \mathbf{A} + \mathbf{A}^{\mathrm{T}} \end{bmatrix} + \frac{1}{2} \begin{bmatrix} \mathbf{A} - \mathbf{A}^{\mathrm{T}} \end{bmatrix} = \operatorname{symm} \mathbf{A} + \operatorname{skew} \mathbf{A}$$

Symmetric part

- A short note regarding the notation,
 - We used **S** to denote the strain-rate tensor and Ω to denote the spin or vorticity tensor.
 - This is the notation that we will consistently use.
 - In the literature, some authors use a different notation.
 - For example, some authors use **D** to denote the strain-rate tensor and **S** to denote the spin tensor.

Comment on non-Newtonian flows

- For some non-Newtonian flows (e.g., polymers, blood, honey, chocolate), the non-Newtonian viscosity η can be written in terms of the strain-rate tensor $\eta(\mathbf{S})$.
- In general, the non-Newtonian viscosity depends on the shear rate magnitude (or the norm),

$$\gamma = \sqrt{2S:S}$$
 This is the scalar product of two second rank tensors. $A:B$

- There are many models to compute the viscous stress tensor in non-Newtonian flows.
- For example, using the power law model, the non-Newtonian viscosity is computed as follows,

$$\eta = k\gamma^{n-1}$$
 • Where *k* (consistency index) and n (power-law index) are input parameters of the model.
• Notice that if you set *n* and *k* equal to 1, you get the Newtonian formulation.

Therefore, the viscous stress tensor can be approximated as follows,

Non-Newtonian flow
$$\rightarrow \tau = \eta(\mathbf{S})\mathbf{S}$$
 where $\mathbf{S} = \frac{1}{2} \begin{bmatrix} \nabla \mathbf{u} + \nabla \mathbf{u}^T \end{bmatrix}$

Simplifications of the governing equations of fluid dynamics

• From now on, and only to reduce the amount of algebra, we will use the incompressible, isothermal, Newtonian, governing equations.

$$\nabla \cdot (\mathbf{u}) = 0$$
$$\frac{\partial \mathbf{u}}{\partial t} + \nabla \cdot (\mathbf{u}\mathbf{u}) = \frac{-\nabla p}{\rho} + \nu \nabla^2 \mathbf{u}$$

Conservative vs. non-conservative form of the governing equations

- We presented the governing equations in their conservative form, that is, the vector of conservative variables is inside the derivatives.
- From a mathematical point of view, the conservative and non-conservative form of the governing equations are the same.
- But from a numerical point of view, the conservative form is preferred in CFD. Specially if we are using the finite volume method (FVM).
- The conservative form enforces local conservation as we are computing fluxes across the faces of a control volume.
- The conservative form use flux variables as dependent variables, and the non-conservative form uses the primitive variables as dependent variables.

$$\frac{\partial\left(\rho\mathbf{u}\right)}{\partial t}+\nabla\cdot\left(\rho\mathbf{u}\mathbf{u}\right)=-\nabla p+\nabla\cdot\boldsymbol{\tau}$$

$$\rho\left(\frac{\partial\left(\mathbf{u}\right)}{\partial t} + \mathbf{u}\cdot\nabla\left(\mathbf{u}\right)\right) = -\nabla p + \nabla\cdot\boldsymbol{\tau}$$

Non-conservative form

- Conservative form
- If you integrate this equation in a control volume, fluxes across the faces will arise.
- The FVM method is based on integrating the governing equations in every control volume.

Conservative vs. non-conservative form of the governing equations

• Let us recall the following identity,

$$abla \cdot (\mathbf{u}\mathbf{u}) = \mathbf{u} \cdot \nabla \mathbf{u} + \mathbf{u}(\nabla \cdot \mathbf{u})$$

• From the divergence-free constraint $\nabla \cdot \mathbf{u} = 0$ it follows that $\mathbf{u}(\nabla \cdot \mathbf{u})$ is equal to zero. Therefore,

$$\nabla \cdot (\mathbf{u}\mathbf{u}) = \mathbf{u} \cdot \nabla \mathbf{u}$$

• Henceforth, the non-conservative form of the momentum equation (also known as the advective or convective form) is equal to,

$$\rho\left(\frac{\partial\left(\mathbf{u}\right)}{\partial t} + \mathbf{u}\cdot\nabla\left(\mathbf{u}\right)\right) = -\nabla p + \nabla\cdot\boldsymbol{\tau}$$

• And is equivalent to the conservative form of the momentum equation (also known as the divergence form),

$$\frac{\partial \left(\rho \mathbf{u}\right)}{\partial t} + \nabla \cdot \left(\rho \mathbf{u} \mathbf{u}\right) = -\nabla p + \nabla \cdot \boldsymbol{\tau}$$

Incompressible Navier-Stokes using index notation

 The incompressible Navier-Stokes equations can also be written using index notation as follows,

$$\frac{\partial u_i}{\partial x_i} = 0$$

$$\frac{\partial u_i}{\partial t} + \frac{\partial u_i u_j}{\partial x_j} = -\frac{1}{\rho} \frac{\partial p}{\partial x_i} + \nu \frac{\partial^2 u_i}{\partial x_j x_j} \qquad \qquad \substack{i = 1, 2, 3\\ j = 1, 2, 3}$$

Incompressible Navier-Stokes using index notation

• Dust your notes on index notation* as from time to time I will change from vector notation to index notation.

$$\nabla \cdot (\mathbf{u}) = 0 \qquad \qquad \frac{\partial u_i}{\partial x_i} = 0$$
$$\frac{\partial \mathbf{u}}{\partial t} + \nabla \cdot (\mathbf{u}\mathbf{u}) = \frac{-\nabla p}{\rho} + \nu \nabla^2 \mathbf{u} \qquad \longleftrightarrow \qquad \frac{\partial u_i}{\partial t} + \frac{\partial u_i u_j}{x_j} = -\frac{1}{\rho} \frac{\partial p}{\partial x_i} + \nu \frac{\partial^2 u_i}{\partial x_j x_j}$$